

Halogenlampe G9
halogen lamp G9
27W / 230V

Erdung 6,3 x 0,8
earth Tab 6,3 x 0,8

LDR, weiß, 0,821 mm², Glasseide-ummantelt,
UL-Style 5561, AWG 18, 550°C, 300V
wire, white, 0,821 mm², glassfibre braided,
UL-Style 5561, AWG 18, 550°C, 300V

Flachsteckhülse 6,3 - 1,5
für Flachstecker 6,3x0,8
St vernickelt
tab receptacle 6,3 - 1,5
for tab terminal 6,3x0,8
steel, nickel plated

Steckergehäuse
insulation housing

1100 ±10

6 ±1

20 ±1

Linse
Borosilicat Glas, 550°C
lens
borosilicate glass, 550°C

Reflektor, St aluminisiert
reflector, steel aluminised

Steatitfassung
lampholder, steatite

Ausschnitt / cut - out

mit Emaille / with enamel t = 0,8 - 1,8

70 ±0,3

55 ±0,3

R 0,5

1:2

80 ±1

65 ±1

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse „G“
This product contains a light source of energy efficiency class "G"

Nur zur Information / Only for information		Datum / Date		Name		Benennung / Title	
Zzeichnung wird bei Änderung nicht ausgetauscht / Drawing will not be replaced when change is made Original vom / Date of Original		Mi 22.06.2022 10:27:16		Mi 19.10.2022 07:43:53		Kundenzeichnung / Drawing for customers	
Maßstab / Scale		Bearb. / By		Name		Benennung / Title	
1 : 1		02.08.16		Klute		BO-Leuchte G9 oven lamp G9	
Alle Maße in Millimeter All dimensions in millimetres		Copyright note ISO 16016		Zeichnung Nr. / Part No.		77.728.0129	
projection method for views		The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.		KUND		3D-Geom. Reference	
BJB GmbH & Co. KG D-59755 Arnsberg (Neheim) Werler Str.1 Tel.: +49 (2932) 982-0		FuE		Ers. / Replaces		01K-A3A-02	
						Rev. - ID.Nr. 01K-A3B-04.dft	