


TALEXdriver ADVANCED LCI TEC | Linear Low Profile

	Output current	Output power	Output voltage range	Input voltage	Efficiency	Size	Order No.
LCI 35W 250mA TEC Ip	250mA	35W	47–140V	220–240V _{ac}	90%	280 x 30 x 21 mm	87500322
LCI 35W 300mA TEC Ip	300mA	35W	47–117V	220–240V _{ac}	89%	280 x 30 x 21 mm	87500323
LCI 35W 350mA TEC Ip	350mA	35W	45–100V	220–240V _{ac}	89%	280 x 30 x 21 mm	87500324
LCI 65W 250mA TEC Ip	250 mA	65W	112–250V	220–240 V _{ac}	93%	280 x 30 x 21 mm	87500325
LCI 65W 300mA TEC Ip	300 mA	65W	97–217V	220–240 V _{ac}	92%	280 x 30 x 21 mm	87500326
LCI 65W 350mA TEC Ip	350 mA	65W	83–186V	220–240 V _{ac}	92%	280 x 30 x 21 mm	87500327

Further details can be found in datasheet.

▼ At a glance: ADVANCED LCI TEC | Linear Low Profile

- ___ Improved output current tolerance +/- 5 %
- ___ Low output current ripple +/- 15 %
- ___ Perfect fit for TALEXmodules LLE G3 and ESSENCE